

Technical Specifications

Straw- and grass bale accumulators

<i>Model</i>	320/3 Straw	320/5 Straw	325 Straw	430/3 Straw/Grass	430/5 Straw/Grass	435 Straw/Grass
Number of bales	3	5	3	3	5	3
Bale width max., m	0,8/0,9	0,8/0,9	1,2	0,8/0,9	0,8/0,9	1,2
Working width, mm	2980	4360	4000	2900	4250	4250
Transport width, mm	2980	2980	2980	2800	2600 (2800)	2600 (2800)
Transport height, mm	1720	1940	1720	2100	2100	2100
Length, mm	3850	3850	3850	2800	2800	2800
Net weight, kg	1400	1500	1450	1020	1480	1320
Payload, kg	2250	2250	2250	2250	2250	2250
Transport width, mm, on truck	2980/2408*	2980/2408*	2980/2408*	2470	2470	2470
Wheels - single (300/65-12/8)	√	√	√	√	√	√
Wheels - dual (300/65-12/8)	Accessory	Accessory	Accessory	Accessory	Accessory	Accessory
Wheels - dual (23x8,5-12)	-	-	-	Accessory	Accessory	Accessory
Computer	√	√	√	√	√	√
Weighing platform	Accessory	Accessory	Accessory	Accessory	Accessory	Accessory
Rolls	-	-	-	√	√	√
Hydraulic sides	Accessory	Accessory	Accessory	-	√	√
Separator sledge	-	-	-	-	-	-
Oil flow, l/min	30	30	30	30	30	30
Oil pressure max., bar	190	190	190	190	190	190
Oil outlets	1 single acting, 1 return	1 single acting, 1 return	1 single acting, 1 return	1 single acting, 1 return	1 single acting, 1 return	1 single acting, 1 return
Hydraulic system	Open centre / closed centre / LS	Open centre / closed centre / LS	Open centre / closed centre / LS	Open centre / closed centre / LS	Open centre / closed centre / LS	Open centre / closed centre / LS
Electrical supply, volt	12	12	12	12	12	12
Colour	optional	optional	optional	optional	optional	optional

*2408mm mounted in transport frame √ = Standard